

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 890)

Set post 4" dia., 4 ft. long, with marked stone 12" in ground for ¼ sec. cor. marked ¼ S on W. face, from which
A Maple 8" dia., bears S.19°E., 30 lks. dist. mkd. ¼ S BT.
A Fir 24" dia., bears N.87°W., 10 lks. dist. mkd. ¼ S BT.

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11384-85)

Proportional measurement.
Set an iron post 3 ft. long, 1" dia., 28" in the ground for ¼ sec. cor. of sec. 18 only, with brass cap mkd. ¼ S 18 1945
from which
A Fir 50" dia., bears N.85½°E., 217 lks. dist. mkd. ¼ S18 BT.
A Fir 34" dia., bears S.39½°E., 143 lks. dist., mkd. ¼ S18 BT.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14209-10)

The ¼ sec. cor. of sec. 18 only, monumented with an iron post 1" dia., extending 6" above ground firmly set, with brass cap mkd. in 1945
from which bearing trees marked in 1945:
A sawed and burned Fir stump 54" dia., bears N.85½°E., 217 lks. dist., with no marks remaining.
A sawed Fir stump 48" dia., bears S.39½°E., 143 lks. dist., with scribe marks ¼ S18 visible on opened blaze.
and new bearing trees:
A Fir 4" dia., bears N.31½°E., 47 lks. dist. mkd. ¼ S18 BT.
A Fir 4" dia., bears S.80°E., 17 lks. dist. mkd. ¼ S18 BT.

Survey by Mark Smalley - For: Roseburg Forest Products - Mar. 18, 1997 - C.S. File 65/15-9

Found - 1945 GLO Iron pipe/brass cap.
15" Fir S.80°E., 17 lks., good, healed face.
14" Fir N.31½°E., 47 lks., good, healed face. Tag 7½ ft. up tree.

(Cont. Next Page)

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 700442

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 18 only, T21-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Root hole N.85½°E., 217 lks., remains of 1945 BT.
New BTs -11" Fir N.4°W., 17.3 ft., scribed ¼ BT.
6" Fir S.12°E., 13 ft. scribed ¼ BT.