

PRIMARY CORNER DESCRIPTION C C for Secs. 12 & 13 only, (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 3 Page(s) 923)

-----

I set Fir post 4 ft. long, 4" sq., 24" in the ground at point of intersection for closing corner to secs. 12 & 13, marked C C T21S on the W.; R9W S13 on the S.; and S12 on the N. faces with 4 grooves on the S. and 2 grooves on the N. sides, from which

- A Fir 6" dia., bears S.12°E., 37 lks. dist. mkd. CC T21S R9W S12 and 13 BT.
- A Fir 8" dia., bears S.30°W., 29 lks. dist. mkd. T21S R9W S13 BT.
- A Hemlock 6" dia., bears N.61°W., 52 lks. dist. mkd. T21S R9W BT.

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11385)

-----

(After a careful investigation, it is developed that Gesner's recorded retracement of this line is entirely fictitious, that it is a deliberate fabrication on his part for the purpose of justifying his own work and creating a limiting boundary for T21S R9W., and is therefore rejected as a suitable basis for restoration of lost corners referring to T21S R8W.) (Vol. 27 Pg. 11379)

The closing cor. of secs. 12 & 13, the badly decayed remains of a wooden stake which shows evidence of axe and scribe marks, lying loose on the ground, near which I unearth the sharpened portion of same.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with remains of marked stake deposited at the base, with brass cap mkd:

	T 21 S	T 21 S
	S 12	R 8 W
C C	S 13	S 18
	R 9 W	
	1945	

from which

- A dead Cedar 50" dia., bears S.28°W., 116 lks. dist., mkd. T21S R9W S13 CC BT. (New BT)
- A Fir 18" dia., bears N.34°W., 251 lks. dist., mkd. T21S R9W S12 CC BT. (New BT)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION C C for Secs. 12 & 13 only, (East)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14210)

-----  
The closing cor., monumented with an iron post, 2" dia., extending 12" above ground, firmly set, with brass cap mkd. in 1945,

from which bearing trees mkd. in 1945:

A sawed Cedar stump 48" dia., bears S.28°W., 116 lks. dist., with no marks remaining.

A Fir snag 20" dia., bears N.34°W., 251 lks. dist., with scribe marks T21S R9W S12 CC BT visible on open blaze.

and new bearing trees:

A Fir 6" dia., bears S.18°W., 44 lks. dist., mkd. T21S R9W S13 CC BT.

A Fir 6" dia., bears N.33°W., 31 lks. dist., mkd. T21S R9W S12 CC BT.

Pg. 14228

From this point the cor. of secs. 7 & 18 only, T21S R8W bears N.0°57'E., 0.97 chs.

-----  
Mark Smalley - For: Roseburg Forest Prod. - Mar. 13, 1997 - C.S. 65/13-9B

Found - 1945 GLO Iron pipe/brass cap.  
50" Cedar stump, S.28°W., 70' burnt stump.  
18" Fir stob, N.34°W., 165.7' scribed visible.  
13" Fir, S.18°W., 44 lks. good healed face.

New Accessories -

10" Fir, N.33°W., 16.5' scribed "S 12 BT".

12" Fir, S.14°E., 16.5' scribed "SC BT".

14" Fir, S.76°E., 21.7' scribed "SC BT".