

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only, T21-8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 890)

Set post 6" dia., 4 ft. long, with marked stone 12" in ground for cor. to secs. 12, 13, 7 and 18, marked T21S S7 on NE.; R8W S18 on SE.; R9W S13 on SW.; S12 on NW. faces with 2 notches on N. and 4 notches on S. edges, from which
A Cedar 10" dia., bears N.67°W., 16 lks. dist. mkd. T21S R9W S12 BT.
A Hemlock 16" dia., bears N.70°E., 47 lks. dist. mkd. T21S R8W S7 BT.
A Hemlock 16" dia., bears S.44°E., 41 lks. dist. mkd. T21S R8W S18 BT.
A Hemlock 8" dia., bears S.63°W., 17 lks. dist. mkd. T21S R9W S13 BT.

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 3 Page(s) 923)

The sec. cor., of 7 & 18, T21S R8W which is a Hemlock Tree 14" dia. marks grown over, from which
A Hemlock 16" dia., bears N.70°E., 45 lks. dist. mkd. T21S R8W S7 BT.
A Hemlock 16" dia., bears S.44°E., 42 lks. dist. mkd. T21S R8W S18 BT.
A Hemlock 16" dia., bears S.58°W., 53 lks. dist. mkd. T21S R9W S13 BT.
A Cedar 12" dia., bears N.57°W., 16 lks. dist. mkd. T21S R9W S12 BT.

The description of this corner does not agree with notes furnished me but after diligent search I could not find any indications of another corner ever having been established. I destroyed marks on the Cedar bearing tree.

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11385-86)

(After a careful investigation, it is developed that Gesner's recorded retracement of this line is entirely fictitious, that it is a deliberate fabrication on his part for the purpose of justifying his own work and creating a limiting boundary for T21S R9W., and is therefore rejected as a suitable basis for restoration of lost corners referring to T21S R8W.) (Vol. 27 Pg. 11379)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only, T21-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

The cor. of secs. 7 and 18, a badly decayed Hemlock stump, 20" dia., with evidence of old axe marks only.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 21 S	T 21 S
R 9 W	S 7
S 12	S 18
	R 8 W
1945	

from which

A dead Hemlock 22" dia., bears N.69½°E., 47 lks. dist., with traces of scribe marks on face of old blaze. (Old BT)

A dead Hemlock 30" dia., bears S.43°E., 44 lks. dist. with traces of scribe marks on face of old blaze. (Old BT)

A dead Hemlock 26" dia., bears S.58°W., 52 lks. dist. with old blaze burned. (Old BT)

A dead Cedar 14" dia., bears S.62½°W., 16 lks. dist. with old blaze burned. (Old BT)

A Fir 20" dia., bears N.18½°E., 45 lks. dist. mkd. T21S R8W S7 BT. (New BT)

A Fir 30" dia., bears S.57½°E., 155 lks. dist. mkd. T21S R8W S18 BT. (New BT)

This sec. cor. is located at foot of descent on W. slope.

BLM Remonumentation of corner by Floyd A. Brooks, Cadastral Surveyor, under Group #350, surveyed Aug. 1960 - (DCSO records Vol. 30 Page(s) 12887)

The sec. cor., determined at record bearing and distance from the remains of the original bearing trees and from the remains of the bearing trees mkd. in 1945:

A turned out Fir 22" dia., bears N.18½°E., 45 lks., with no marks remaining on burned and rotted blaze. (1945)

The decayed remains of a Hemlock stump, bears N.69½°E., 47 lks. dist., with no marks remaining. (Orig)

A turned out Fir 32" dia., bears S.57¼°E., 155 lks. dist. with scribe marks T21S R8W visible on unhealed blaze. (1945)

The decayed remains of a Hemlock stump, bears S.43°E., 44 lks. dist., with no marks remaining. (Orig.)

The decayed remains of a Hemlock stump, bears S.58°W., 52 lks. dist., with no marks remaining. (Orig.)

At the corner point

Reset the iron post 36" long, 2" dia., which had been pulled up and was lying on the ground, 30" in the ground, with brass cap as marked in 1945,

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18 only, T21-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which new bearing trees:
A Fir 3" dia., bears S.87°E., 74 lks. dist. mkd. BT only.
A Fir 3" dia., bears S.43½°E., 38 lks. dist. mkd. BT only.
No other suitable bearing tree available.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14210-11)

The sec. cor., monumented with an iron post 2" dia., extending 6" above ground firmly set, with brass cap mkd. in 1945,
from which bearing trees mkd. in 1945:
A burned and rotted Fir stump 26" dia., bears N.18½°E., 45 lks. dist., with no marks remaining.
The root hole of a fallen Fir 32" dia., bears S.57½°E., 155 lks. dist., with scribe marks 21S R8W S1 visible on open blaze.
and bearing trees mkd. by Floyd A. Brooks in 1960:
A Fir 5" dia., bears S.87°E., 74 lks. dist., with healed blaze.
A Fir stump 3" dia., bears S.43½°E., 38 lks. dist., with scribe marks BT visible on partly healed blaze.
and new bearing trees:
A Fir 4" dia., bears N.74½°E., 16 lks. dist., mkd. T21S R8W S7 BT.
A Fir 5" dia., bears S.35°E., 34 lks. dist. mkd. T21S R8W S18 BT.
Pg. 14228
From this point the cor. of secs. 12 & 13 only, T21S R9W bears S.0°57'W., 0.97 chs.

Survey by Mark F. Smalley - For: Roseburg Forest Products - Mar. 13, 1997 - C.S. File 65/13-9A&B

Found - 1945 GLO IPBC
20" Fir, N.18°E., 29.7', down and rotten.
30" Fir, S.57°E., 102.3', down and rotten.
12" Fir, S.35°E., 34 lks., snag.
13" Fir, N.74½°, 16 lks., good-healed face
6" Fir, S.87°E., 74 lks., snag

New Accessories -
13" Fir, S.11°E., 20' scribed "S 18 BT".
16" Fir, S.18°W., 18.8' scribed "SC BT".
11" Fir, N.4°W., 18.3' scribed "SC BT".