

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14213-14)

-----  
Point for the ¼ sec. cor. of sec. 1 only, T21S R9W.  
Set a fiber glass post 28" long, 2½" dia., 24" in the ground with brass cap mkd:

T 21 S  
¼ S 1  
R 9 W  
1967

from which

A sawed and burned Fir stump 30" dia., bears S.39°W., 20½ lks. dist., mkd. ¼ S1 BT.

A rock outcropping, bears N.87°W., 39½ lks. dist. mkd. X BO.

From this point, United States Coast and Geodetic Survey triangulation station SCARE 1953, bears N.60°57'W., 10.51 chs. dist., monumented with a standard brass cap, 3½" dia., firmly set in a concrete post 10" dia., extending 6" above ground with top mkd. SCARE 1953, and a triangle.