

PRIMARY CORNER DESCRIPTION NW. Cor. for Sec. 6, T21-8

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 2 Page(s) 892)

 Set post 6" dia., 4 ft. long, 24" in ground for cor. to Tps. 20 & 21 S R 8 & 9 W marked T20S S31 on NE.; R8W S6 on SE.; T21S S1 on SW.; R9W S36 on NW. faces with 6 notches on each side, from which
 A Fir 12" dia., bears N.61°W., 23 lks. dist. mkd. T20S R9W S36 BT.
 A Fir 12" dia., bears S.68°W., 31 lks. dist. mkd. T21S R9W S1 BT.
 A Fir 6" dia., bears S.31°E., 35 lks. dist. mkd. T21S R8W S6 BT.
 A Dogwood 6" dia., bears N.27°E., 19 lks. dist. mkd. T20S R8W S31 BT.

Cor. Fd. and used in GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 892-93)

GLO Resurvey by Norman D. Price and George Rigby, Cadastral Engineers, under Group #282, Surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11388)

 The cor. of Tps. 20 & 21 S., R 8 W, the locus of which is determined at the record bearing and distance from the original NW. bearing tree.

At the corner point
 Set an iron post, 3 ft. long, 3" dia., 28" in the ground, with brass cap mkd:

	T 20 S	
	R 8 W	
T 21 S	S 31	
R 9 W	S 6	
S 1	T 21 S	
	1945	

from which
 A Fir 46" dia., bears N.61°W., 28 lks. dist., the surface scar of the tree, its kind and position agree with the official record; I do not uncover the marks.
 A Fir 36" dia., bears N.56½°E., 84 lks. dist., mkd. T20S R8W S31 BT. (New BT)
 A Fir 30" dia., bears S.74°E., 95 lks. dist., mkd. T21S R8W S6 BT. (New BT)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION NW Cor. for Sec. 6, T21-8

Alias	Description

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14214)

The Tsp. cor., monumented with an iron post 3" dia., extending 8" above ground, firmly set, with brass cap marked in 1945,
from which an original bearing tree:
A decayed and burned Fir snag 40" dia., bears N.61°W., 28 lks. dist., with no marks remaining.
and bearing trees marked in 1945:
A Fir snag 55" dia., bears N.56½°E., 84 lks., dist. with healed blaze.
A Fir, 38" dia., bears S.74°E., 105 lks. dist. with fragmentary scribe marks visible on burned face of partly healed blaze. (Rec. 95 lks.)

Gary Smither - Dec. 2000 - C.S. File 65/33-23

Found - 1945 brass cap on iron pipe firmly set with red steel fence post driven alongside the brass cap.
A decayed & burned Fir snag, 7 ft. tall, bears N.61°W., 28 lks., orig. BT w/no mks remaining.
55" Fir stump bears N.56½°E., 84 lks., with tag, 1945 BT.
30" Fir taken in 1945 at S.74°E., 105 lks., is **gone**.
New BTs- 13" Fir, N.41°E., 18.3 ft. to spike driven in side center, mkd: "T20 R8 S31 BT" with BT tag.
6" Fir, S.18°E., 14.9 ft. to spike driven in side center, mkd: "T21 R8 S6 BT" with BT tag.
7" Fir, S.71°W., 17.1 ft. to spike driven in side center, mkd: "T21 R8 S6 BT" with BT tag.
15" Fir, North 23.0 ft. to spike driven in side center, mkd: "T20 R8 S31 BT" with BT tag.

Fd ok 10/2019 - R. Quimby - C.S. File 65/104-22