

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 31, T21-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 - (DCSO records Vol. 3 Page(s) 1192-93)

I set a sandstone in the ground, for closing cor. to townships 21 S., Ranges 10 and 11 W., (8.25 chs. E. of cor. to Tp. 22 S., R.10 & 11 W.) marked C C with 6 notches on N, E, and W. edges, and raised a mound of stone 1½ ft. high, 2 ft. base, alongside, pits impracticable.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1050)

Apportioned Distance.
Set an Iron post, 3 ft. long, 3" dia., 24" in the ground, for closing cor. of Tps. 21 S., Rs. 10 and 11 W., with brass cap marked:
CC
T21S
R11W R10W
S36 S31
1919

from which
A Fir 12" dia., bears N.66°E., 25 lks. dist. mkd. C C T21S
R10W S31 BT.
A Fir 10" dia., bears N.70°W., 7 lks. dist. mkd. C C T21S
R11W S36 BT.

Fd. cor. Jan. 1958 by G.R. Lecklider - M 8-29

Survey by James W. Prochnau PLS #1305 - For: U.S. Forest Service - July 1985 - M 99-21 A&B

Found - 3½" brass cap on 2½" iron pipe set by GLO. 1919
20" D.Fir bears N.66°W., 4.2 ft. (Rec. N.70°W., 4.6 ft.) healed.
Unrecorded BT, 11" D.Fir bears N.86°E., 5.8 ft., healed.