

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 135500

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 18 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1140)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ Sec. cor., of Sec. 18 only with brass cap mkd:

¼
S 18
1919

from which

- A Fir, 30" dia., bears S.62°E., 17 lks., mkd: ¼ S18 BT.
- A Cedar, 12" dia., bears S.48°W., 14 lks., mkd: ¼ S18 BT.

Herman A. Pieske, RLS #1651 - For: USFS - Nov. 1984 - M 97-77
A & B

Set - 2½" x 30" alum. pipe 12" in the ground to bedrock with mound of stone, with 3¼" alum. cap mkd: "USDA Forest Service T21S R10W ¼ S18 RLS 1651 1984 Unlawful to Disturb"

18" D.Fir bears S.20°W., 21.2 ft. blazed & scribed "¼ S18 BT"

8" D.Fir bears S.76°E., 8.6 ft. blazed & scribed "¼ S18 BT"