

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 137100

PRIMARY CORNER DESCRIPTION North 1/4 Cor. for Sec. 6 only, T22-10

Alias <u>935010</u>	Description <u>Cor. #1, HES #130</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 279, dated March 5, 1878 - (DCSO records Vol. 4 Page(s) 1740)

-----  
Marked a Fir, 10" dia. for ¼ sec. cor., from which  
A Fir 6" dia., bears S.10°E. 92 lks. dist.  
A Fir 5" dia., bears N.87°W., 16 lks. dist.

Cor. Fd. and used in GLO survey by Aurelius Todd, Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1745, 1754 and 1766)

Extracts for Homestead Entry Survey Survey No. 130, made by Frank D. Maxwell, Surveyor Forest Service, under Special Instructions dated March 12, 1914 - (DCSO records Vol. 5 Page(s) 1850)

-----  
At the ¼ sec. cor. on the N. bdy. of Sec. 6, which is a Fir tree, 26" dia., marked and witnessed as described by the Surveyor General.  
In cutting into this corner tree and bearing trees in order to read the markings, I spoil the readings somewhat, so Remark the corner as follows:  
A Fir 26" dia., (orig.) marked ¼ S6 on S. face, from which,  
A Fir 24" dia., bears S.10°00'E., 93 lks. dist. (orig.)  
This tree partially destroyed, marking left on tree.  
A Fir 8" dia., bears S.26°10'E., 55 lks. dist. (New)  
marked ¼ S6 BT.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1049)

-----  
Intersect the old ¼ sec.cor. of sec. 6, which is a Fir, 26" dia., marked and witnessed as described by the Surveyor General. This corner is identical with cor. No. 1, H.E.S. No. 130.