

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 31 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1049)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for
¼ sec. cor. of sec. 31 only, with brass cap mkd: ¼ $\frac{S31}{1919}$

from which,

A Hemlock 36" dia., bears N.2°E., 44 lks. dist. mkd. ¼ S31
BT.

A Fir 40" dia., bears N.60°W., 29 lks. dist. mkd. ¼ S31
BT.

Survey by James W. Prochnau, PLS #1305 - For: U.S. Forest Service - Aug. 1985 - M 99-21 A&B

Found - A 1" Iron pipe, set by GLO in 1919.
56" Hemlock bears N.2°E., 29.0 ft., rotten face.
50" D.Fir stump bears N.60°W., 19.1 ft., visible
scribe.

Set a U.S. Dept. of Agriculture brass cap, mkd: T21S R10W ¼
S31 T22S R10W PLS 1305 1985.