

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 7 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1140)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ Sec. cor. of Sec. 7 only, with brass cap mkd:

¼ $\frac{S 7}{1919}$

from which

A Cedar , 20" dia., bears N.5°E., 72 lks., mkd: ¼ S7 BT.

A Hemlock, 12" dia., bears N.29°W., 39 lks., mkd: ¼ S7 BT.

Herman A. Pieske, RLS #1651 - For: USFS - Nov. 1984 - M 97-77
A & B

Set - 2½" x 30" alum. pipe 12" in the ground to bedrock with mound of stone, with 3¼" alum. cap mkd: "USDA Forest Service T21S R10W ¼ S7 RLS 1651 1984 Unlawful to Disturb"

24" D.Fir bears N.24°W., 49.7 ft., blazed & scribed "¼ S7 BT"

18" D.Fir bears N.8°E., 96.4 ft., blazed & scribed "X BT"