

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 177477

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 18 & WNW Cor. Sec. 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1139)

A point 74.92 chs. East of the cor. of secs. 7, 12, 13, & 18, on W bdy, of Township. Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 17 & 18, with brass cap
mkd:

T21S R10W
S 18|S 17
1919

from which

An Alder, 16" dia., bears S.1°E., 52 lks., mkd: T21S R10W S17 BT.

A Cedar, 60" dia., bears S.60°W., 28 lks., mkd: T21S R10W S18 BT.

Herman A. Pieske, RLS #1651 - For: USFS - Nov. 1984 - M 97-77 A & B

Found - 2" IP well rusted & filled with concrete, 1919 concrete, 1919 brass cap broken off, not found.
66" Cedar bears S.60°W., 18.5 ft., good scar.

Set - 2½"x30" alum. pipe over iron pipe, 24" in ground with ¾" alum. cap mkd: "US Dep of Agri-Forest Service T21S R10W S7 S18 S17 RLS 1651 1983 Unlawful to Disturb". Buried pipe alongside.
16" Hemlock bears S.61°E., 154.2 ft. blazed & scribed "T21S R10W S17 BT"