

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs. 29, 30, 31, & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1130)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 29, 30, 31 & 32, with brass cap mkd:

T21S R10W
S 30|S 29
S 31|S 32

from which

- A Fir, 6" dia., bears N.23°E., 25 lks., mkd: T21S R10W S29 BT.
- A Fir, 12" dia., bears S.5°E., 11 lks., mkd: T21S R10W S32 BT.
- A Fir, 10" dia., bears S.88°W., 9 lks., mkd: T21S R10W S31 BT.
- A Fir, 10" dia., bears N.27°W., 12 lks., mkd: T21S R10W S30 BT.