

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1103-4)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 19, 20, 29 & 30, with brass cap mkd:

T21S R10W
S 19|S 20
S 30|S 29
1919

from which

- A Fir, 18" dia., bears N.51°E., 22 lks., mkd: T21S R10W S20 BT.
- A Fir, 15" dia., bears S.53°E., 24 lks., mkd: T21S R10W S29 BT.
- A Fir, 18" dia., bears S.83°W., 24 lks., mkd: T21S R10W S30 BT.
- An Alder, 12" dia., bears N.24°W., 57 lks., mkd: T21S R10W S19 BT.