

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1135)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 17, 18, 19, & 20, with brass cap mkd:

T21S R10W
S 18|S 17
S 19|S 20
1919

from which

- An Alder, 30" dia., bears N.15°E., 103 lks., mkd: T21S R10W S17 BT.
- A Hemlock, 10" dia., bears S.56°E., 50 lks., mkd: T21S R10W S20 BT.
- A Maple, 12" dia., bears S.33°W., 93 lks., mkd: T21S R10W S19 BT.
- An Alder, 18" dia., bears N.64°W., 54 lks., mkd: T21S R10W S18 BT.