

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 200477

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 7 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1140-1)

(A point due South of the cor. of secs. 5, 6, 7, & 8) Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for SE cor. of sec. 7 with brass cap mkd:

T21S|
R10W|
S 7|
1919

from which

A Fir, 30" dia., bears N.87°W., 59 lks., mkd: T21S R10W S7 BT.

A Hemlock, 8" dia., bears N.15°W., 45 lks., mkd: T21S R10W S7 BT.

Herman A. Pieske, RLS #1651 - For: USFS - Nov. 1984 - M 97-74 A & B

Found - 2" IP with 2½" brass cap properly mkd. 1919
46" D.Fir bears N.87°W., 38.9 ft., shows good scar.
New BT - 40" Maple bears S.15°E., 20.8 ft., blazed & scribed
"T21S R10W S17 BT"