

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION SW Cor. Sec. 8 & NNW Cor. Sec. 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1142-3)

-----  
(A point due West of cor. of secs. 8, 9, 16, & 17) Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 8 & 17, with brass cap mkd:

|T21S  
|S 8  
|S 17  
|R10W  
1919

from which

A Fir, 40" dia., bears N.71°E., 77 lks., mkd: ¼ S8 BT.

An Alder, 12" dia., bears S.67°E., 36 lks., mkd: ¼ S17 BT.

Herman A. Pieske, RLS #1651 - For: USFS - Nov. 1984 - M 97-74  
A & B

-----  
Found - 2" IP with 1919 GLO 2½" brass cap properly mkd., rusted & broken.

39" D.Fir windfall bears S.88°E., 45.6 ft., to approx. position of root hole. Tree slid downhill. OBT

Set - 2½"x30" alum. pipe 6" above ground with ¾" alum. cap mkd: "USDA FOREST SERVICE T21S R10W S7 S8 S17 RLS 1651 1983 UNLAWFUL TO DISTURB". Buried brass cap alongside.

64" D.Fir bears N.80°E., 33.1 ft. blazed & scribed "T21S R10W S8 BT"

13" Bigleaf Maple bears S.80°E., 45.1 ft., blazed & scribed "T21S R10W S17 BT"