

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 3 Page(s) 1002)

-----  
Set stone 26x14x6 for corner to Secs. 5, 6, 7, & 8.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1141-2)

-----  
Intersect E & W line, at the cor. of secs. 5, 6, 7, & 8, which is a stone, marked as described by the Surveyor General. Alongside the old stone Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 5, 6, 7, & 8, with brass cap mkd:

T21S R10W  
S 6 | S 5  
S 7 | S 8  
1919

from which

- A Cedar, 40" dia., bears N.34°E., 90 lks., mkd: T21S R10W S5 BT.
- A Fir, 36" dia., bears S.78°E., 67 lks., mkd: T21S R10W S8 BT.
- A Cedar, 14" dia., bears S.30°W., 74 lks., mkd: T21S R10W S7 BT.
- A Fir, 40" dia., bears N.32°W., 80 lks., mkd: T21S R10W S6 BT.

Herman A. Pieske, RLS #1651 - For: Siuslaw National Forest USDA - Nov. 1983 - M 95-59 A & B

- 
- Found - 1" IP filled with concrete & rusted & broken off, with 2½" brass cap. (1919 GLO cap properly mkd.)
- 36" Fir stump bears S.78°E., 27.0 ft., (Rec. 44.2 ft.) shows fragmentary marks.
  - 16" Cedar snag bears S.20°W., 45.4 ft. (Rec. S.30°W., 48.8 ft.) shows open face, no marks but "H" carved in bark above face.
  - 40" Fir stump bears N.32°W., 47.6 ft., (Rec. 52.8 ft) shows no marks.
  - 40" Cedar snag bears N.34°E., 55. 2 ft. (Rec. 59.2 ft) no visible marks.

continued next page

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7 & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set - 2½" x 30" alum. pipe at position of found pipe, 24" in the ground, with mound of stone, with 3¼" alum. cap mkd: US DEP OF AGRI-FOREST SERVICE T21S R10W S6 S5 S7 S8 RLS 1651 1983 UNLAWFUL TO DISTURB.  
10" D.Fir bears S.48½°W., 9.1 ft., blazed & scribed: T21S R10W S7 BT  
16" D.Fir bears N.44°W., 24.3 ft., blazed & scribed: T21S R10W S6 BT  
8" D.Fir bears N.44½°E., 44.2 ft., blazed & scribed: T21S R10W S5 BT  
10" D.Fir bears S.41°E., 18.6 ft., blazed & scribed: T21S R10W S8 BT

Fd. Ok by David Wellman - 5/2005 - M147-72