

PRIMARY CORNER DESCRIPTION N. sec. cor. for 5 and 6 only, T22-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1753-54)

I set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 5 and 6, marked S5 on E.; T22S R10W on S.; S6 on W., with 5 notches on E. and 1 notch on W. faces, from which,
An Alder 8" dia., bears N.40°E., 33 lks. dist. mkd. T22S R10W S5 and 6 BT.
An Alder 4" dia., bears S.25°E., 28 lks. dist. mkd. T22S R10W S5 BT.
A Fir 36" dia., bears S.82°W., 50 lks. dist. mkd. T22S R10W S6 BT.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1047-48)

Intersect the old cor. of secs. 5 and 6, which is a decayed post, marked and witnessed as described by the Surveyor General. Alongside the old cor., Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 5 and 6, with brass cap marked:

S6 S5
T22S R10W
1919

from which

A Fir 8" dia., bears S.49°E., 21 lks. dist. mkd. T22S R10W S5 BT. (New BT)
A Fir 42" dia., bears S.82°W., 50 lks. dist. mkd. T22S R10W S6 BT. (Old BT)