

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 235500

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 17 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1144)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ Sec. cor., with brass cap mkd:

¼
 S 17
 1919

from which

An Alder, 12" dia., bears S.12°E., 23 lks., mkd: ¼ S17 BT.
A Fir, 50" dia., bears S.72°W., 22 lks., mkd: ¼ S17 BT.

Herman A. Pieske, RLS #1651 - For: USFS - Nov. 1984 - M 97-77
A & B

Found - 1" IP filled with concrete and broken off, a 2½" brass cap properly mkd. lying alongside (1919)
70" D.Fir bears S.72°W., 14.5 ft. (to center of tree) well healed scar.
36" Alder windfall, roothole bears S.12°E., 15.2 ft.
Set - 2½" x 30" alum. pipe over found IP with 3¼" alum. cap mkd: "USDA Forest Service T21S R10W ¼ S17 RLS 1651 1984 Unlawful to Disturb" Buried brass cap alongside.
34" D.Fir bears S.71°E., 58.4 ft. blazed & scribed "¼ S17 BT"