

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 8 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1143-4)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 Sec. cor. of Sec. 8 only, with brass cap mkd:

1/4 S 8
1919

from which

- A Fir, 18" dia., bears N.33°W., 10 lks., mkd: 1/4 S8 BT.
- A Fir, 12" dia., bears N.58°E., 74 lks., mkd: 1/4 S8 BT.

Herman A. Pieske, RLS #1651 - For: USFS - Nov. 1984 - M 97-77
A & B

Set - At proper position, 2 1/2" x 30" alum. pipe 26" in the ground with sandstone mound, with 3 1/4" alum. cap mkd:
"USDA Forest Service T21S R10W 1/4 S8 RLS 1651 1984
Unlawful to Disturb"
16" Hemlock bears N.88°W., 36.3 ft. blazed & scribed
"1/4 S8 BT"
12" D.Fir bears N.79°E., 55.8 ft. blazed & scribed "1/4
S8 BT"