

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 5; & 32, T20-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 12, 1867 (DCSO records Vol. 1 Page(s) 174)

Set post for ¼ sec. corner; from which
An Alder 12" dia., bears S.48°E., 32 lks. dist.
An Alder 15" dia., bears N.40°E., 18 lks. dist.

Survey by Herman Pieske, LS 1651 - For: U.S. Dept. of Agriculture-Forest Service, Siuslaw National Forest - Nov. 1983 - M 95-59 A&B

Set 2½" x 30" alum. pipe 24" in the ground with a 3¼" cap mkd. "US Dept of Agri-Forest Service T20S ¼ S32 S5 T21S RLS 1651 1983 Unlawful to Disturb".
New BTs- 28" Hemlock bears N.28°E., 57.2 ft. scribed ¼ S32 BT
40" Hemlock bears S.9°W., 59.4 ft. scribed ¼ S5 BT.

Fd. Ok by David Wellman - 5/2005 - M147-72