

PRIMARY CORNER DESCRIPTION North 1/4 Cor. for Sec. 5 only, T22-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1753)

Set a Post 4 ft. long, 4" sq., for ¼ sec. cor. marked ¼ S. on N. face, from which,
A Fir 48" dia., bears N.10°W., 70 lks. dist. mkd. ¼ S BT.
A Willow 6" dia., bears S.10°W., 110 lks. dist. mkd. ¼ S BT.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1046-47)

Apportioned Distance.
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ sec. cor. of sec. 5 only, with brass cap marked: ¼ _____
S 5
1919
from which
A Wild Cherry 6" dia., bears S.83°E., 24 lks. dist. mkd. ¼ S5 BT.
An Alder 8" dia., bears S.20°W., 25 lks. dist. mkd. ¼ S5 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - May 1968 - C.S. File 54/1-30

Found - 1919 GLO brass cap, buried and broken off, concrete filled iron pipe in place.
6" now 8" Cherry, down and decayed, laying across I.P., S.83°E., 15.8 ft., no scribe found.
8" now 18" Alder, alive, S.25°W., (Rec. S.20°W.) 16.5 ft., shows scar, do not open. Rescribed in bark "¼ S5 CS BT"

Set Brass cap at cor. mkd: County Surveyors Office
T21S
T22S R10W ¼ _____
1968 S 5

Deposit old corner material alongside.
New BTs -26" D.Fir S.21°W., 39.7 ft. mkd. ¼ S5 CS BT.
14" D.Fir S.42°W., 58.5 ft. mkd. ¼ S5 CS BT.
This corner lies 297 ft. W. of U.S.F.S. line, tag on top of ridge, sloping NW.