

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1118-9)

-----  
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 28, 29, 32 & 33, with brass cap mkd:

T21S R10W  
S 29|S 28  
S 32|S 33  
1919

from which

- A Fir, 6" dia., bears N.61°E., 40 lks., mkd: T21S R10W S28  
BT.
- A Fir, 12" dia., bears S.62°E., 9 lks., mkd: T21S R10W S33  
BT.
- A fir, 4" dia., bears S.10°W., 42 lks., mkd: T21S R10W S32  
BT.
- A Fir, 15" dia., bears N.86°W., 6 lks., mkd: T21S R10W S29  
BT.