

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION West 1/4 Cor. Sec. 21 only

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1122)

-----  
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for  
¼ Sec. cor. of Sec. 21 only, with brass cap mkd:

¼  
|S 21  
1919

from which

- A Hemlock, 5" dia., bears N.35°E., 12 lks., mkd: ¼ S21 BT.
- A Fir, 28" dia., bears S.14°E., 11 lks., mkd: ¼ S21 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones - W. Penley - 10/1/1969 - C.S. File 54/1-38

-----  
Found - Remains of iron rod for brass cap at corner, 1919  
brass cap gone.  
12" now 13" Hemlock, N.35°E., 7.9 ft., shows good  
scar.

32" now 32" D.Fir, S.14°E., 7.3 ft. shows good scar.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T21S R10W  
OFFICE 1969 |S 21 ¼

Bearing trees OK & tagged.