

PRIMARY CORNER DESCRIPTION Cor. Secs. 16 & 21 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Thiel under contract 342 dated Oct. 6, 1879 - (DCSO records Vol. 3 Page(s) 1012)

Set a rock, (pointed) 24"x18x6 at foot of cliff 5 ft. high, for corner to secs. 16, 17, 20, & 21, from which
A Maple, 5" dia., bears N.23°E., 25 lks.
A Fir, 10" dia., bears S.73°E., 42 lks.
An Alder, 8" dia., bears N.30°W., 43 lks.
No trees accessible, SW.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1123-4)

Intersect the old cor. of secs. 16, 17, 20, & 21, which is a stone, marked & witnessed by the old SE BT as described by the Surveyor General. I change this cor. to refer to Secs. 16 & 21 only & alongside the old stone set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 16 & 21, with brass cap mkd:
|T21S
|S 16
|S 21
|R10W
1919

from which
A Maple, 7" dia., bears N.25°E., 24 lks., mkd: T21S R10W S16 BT. (New BT)
A Fir, 14" dia., bears S.73°E., 42 lks., mkd: T21S R10W S21 BT. (Old BT)

Herman A. Pieske, RLS #1651 - For: USFS, Cooked Wassen Cadastral Survey - Aug. 1984 - M 97-33 A & B

Found - 2" iron pipe with concrete stem. Brass cap missing.
10" Maple bears N.23°E., 16.5 ft. (Orig. 7" BT, rec. N.25°E., 15.4 ft) with healed face.
14" Fir snag bears S.73°E., 27.7 ft. (OBT) (rec. 27.5 ft) with healed face.
Set - 2½"x30" alum. pipe, 18" in the ground with ¾" alum. cap mkd: "US Dep. of Agri-Forest Service T21S R10W S16 S21 RLS 1651 1983 UNLAWFUL TO DISTURB"
8" D.Fir bears S.18°E., 3.2 ft., scribed "T21S R10W S21 BT". Tree is on top of rock bluff 8 ft. above corner.