

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 300402

PRIMARY CORNER DESCRIPTION Cor. Secs. 17 & 20 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1124)

-----  
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 17 & 20, with brass cap mkd:

T21S|  
S 17|  
S 20|  
1919

from which

- A Hemlock, 10" dia., bears S.67°W., 74 lks., mkd: T21S R10W S20 BT.
- A Hemlock, 30" dia., bears N.29°W., 36 lks., mkd: T21S R10W S17 BT.

Herman A. Pieske, RLS #1651 - For: USFS, Cooked Wassen Cadastral Survey - Aug. 1984 - M 97-33 A & B

-----  
Found - 2" iron pipe with cap broken off. Concrete stem is all that remains.

- 36" Hemlock bears N.29°W., 23.8 ft. (OBT 30")
- 16" Hemlock bears S.64°W., 36.5 ft. (OBT 10" rec. S.67°W., 48.8 ft) with healed face.

Set - 2½"x30" alum. pipe, 18" in the ground with ¾" alum. cap mkd: "US Dep. of Agri-Forest Service T21S R10W S17 S 20 RLS 1651 1983 UNLAWFUL TO DISTURB"