

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #202, dated March 11, 1874 - (DCSO records Vol. 3 Page(s) 1010)

-----  
Marked a Pyramidal stone, 2 ft. by 3 ft. 20: above ground for corner to secs. 8, 9, 16, & 17 from which  
A Maple, 5" dia., bears N.20°E., 14 lks.  
No other trees near.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1126)

-----  
Intersect the old cor. of secs. 8, 9, 16, & 17, which is a stone, firmly set, marked as described by the Surveyor General. The Orig. NE BT has entirely disappeared. Alongside the old cor. stone set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 8, 9, 16 & 17, with brass cap mkd:  
T21S R10W  
S 8|S 9  
S 17|S 16  
1919

from which  
A Maple, 12" dia., bears N.61°E., 13 lks., mkd: T21S R10W S9 BT.  
A Fir, 12" dia., bears S.71°E., 42 lks., mkd: T21S R10W S16 BT.  
An Alder, 12" dia., bears S.24°W., 35 lks., mkd: T21S R10W S17 BT.  
A Fir, 12" dia., bears N.38°W., 31 lks., mkd: T21S R10W S8 BT.

Richard J. Hintz, PLS #497 - For: International Paper Co. & USFS - Aug. 1983 - M 95-4

-----  
Found - 1919 GLO IP with properly mkd. brass cap & stone alongside.  
16" Maple bears N.73°E., 8.0 ft. (rec. N.61°E., 8.6 ft) 1919 BT  
24" Fir bears S.69°15'E., 27.4 ft. (rec. S.71°E., 27.7 ft.) 1919 BT  
SW Alder BT is gone.  
NW Fir BT is down.  
New BTs- 28" Fir bears S.75°30'W., 21.8 ft. scribed: S17 BT.  
20" Fir bears N.12°45'W., 42.5 ft. scribed: S8 BT.

continued next page

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Herman A. Pieske, RLS #1651 - For: USFS, Cooked Wassen  
Cadastral Survey - Aug. 1984 - M 97-33 A & B

-----  
Found - GLO iron pipe with 1918 brass cap broken off & stone  
          alongside.  
          16" Maple bears N.73°E., 8.0 ft. (Rec. N.61°E., 8.6  
          ft) 1919 BT  
          24" Fir bears S.69°E., 27.4 ft. (Rec. S.71°E., 27.7  
          ft) 1919 BT  
          28" Fir bears S.58°E., 21.8 ft scribed "S17 BT" 1983  
          20" Fir bears N.13°W., 42.5 ft. scribed "S8 BT" 1983  
Set - 2½"x30" alum. pipe, 20" in the ground with ¾" alum.  
      cap mkd: "US Dep. of Agri-Forest Service T21S  
          R10W S8 S9 S17 S16 RLS 1651 1983 UNLAWFUL TO  
          DISTURB".  
      Buried iron pipe and stone alongside.