TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 3 Page(s) 1004)

Set ¼ sec. cor. from which:
A Fir, 5" dia., bears N.20°E., 6 lks.
A Maple, 8" dia., bears N.80°W., 20 lks.

GLO survey by W.H. Byars under contract #202, dated March 11, 1874 - (DCSO records Vol. 3 Page(s) 1010)

Old post for ¼ sec. corner, from which
A Maple, 8" dia., bears N.40°E., 45 lks.
A Maple, 8" dia., bears S.45°W., 37 lks.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1068 & 1126-7)

Pg. 1068
Retracing the line between 8 & 9, no trace of ¼ sec. cor., set temp. ¼ cor.
Pg. 1126-7
Apportioned distance
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ Sec. cor., with brass cap mkd:

¼
S 8|S 9
1919

from which
An Alder, 12" dia., bears N.11°E., 74 lks., mkd: ¼ S9 BT.
An Alder, 10" dia., bears N.43°W., 40 lks., mkd: ¼ S8 BT.

Richard J. Hintz, PLS #497 - For: International Paper Co. & USFS - Aug. 1983 - M 95-4

Found - 1919 GLO iron pipe with brass cap, broken off & lying at the base of the IP.
18" Alder bears N.43°W., 27.0 ft. (rec. 26.4 ft) 1919 BT, bark scribing plainly visible.
No trace of NE Alder 1919 BT.
Set - 1¼" x 36" iron pipe with brass cap stamped: PLS 497 ¼ S8 • S9 1983 T21S R10W, over the remains of the GLO IP.
20" Alder bears N.23°45'E. 43.1 ft. scribed: ¼ S9 BT