

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 3 Page(s) 1001)

Set stone, 24x18x12 for corner to secs. 4, 5, 8, & 9, from which:

An Alder, 12" dia., bears N.12°E., 37 lks.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1127)

Intersect the old cor. of secs. 4, 5, 8, & 9, which is a stone, loosely set, marked & witnessed as described by the Surveyor General. Alongside the old cor. set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 4, 5, 8 & 9, with brass cap mkd:

T21S R10W  
S 5 | S 4  
S 8 | S 9  
1919

from which

An Alder, 30" dia., bears N.12°E., 37 lks., mkd: T21S R10W S4 BT. Old BT

A Maple, 30" dia., bears S.8°E., 77 lks., mkd: T21S R10W S9 BT.

A Cedar, 14" dia., bears S.36°W., 66 lks., mkd: T21S R10W S8 BT.

A Cedar, 24" dia., bears N.32°W., 41 lks., mkd: T21S R10W S5 BT.

Richard J. Hintz, PLS #497 - For: International Paper Co. - Feb. 1982 - M 91-24

Set - 1¼" IP with BC stamped: "PLS 497" from which:  
(1919) 24" Cedar now 48" stump bears N.32°W., 25.9 ft. to 50d nail in face.  
30" Alder bears S.69°45'E., 34.1 ft.  
12" Maple bears N.59°30'W., 7.0 ft.

Richard J. Hintz, PLS #497 - For: International Paper Co. & USFS - Aug. 1983 - M 95-4

Found - 1919 GLO IP with brass cap broken off and lying on rock mound.  
34" Cedar stump bears N.34°W., 26.4 ft. (rec. N.32°W., 27.1 ft.) 1919 BT continued next page

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

24" uprooted Cedar bears S.36°W., 32.0 ft. 1919  
No trace of NE & SE 1919 BTs.  
New BTs- 30" Alder bears S.48°45'E., 39.5 ft. scribed: S9 BT.  
12" Maple bears S.39°W., 12.9 ft. scribed: S8 BT.  
Tie my iron pipe, M 91-24, S.7°19'W., 15.07 and then remove.

Herman A. Pieske, RLS #1651 - For: Siuslaw National Forest  
USDA - Nov. 1983 - M 95-59 A & B  
-----  
Found - 1½" iron pipe filled with concrete and rusted  
through with 2½" brass cap next to. Found rock  
mound around pipe. Cap is 1918 GLO cap.  
30" Alder bears S.50°E., 40.3 ft., shows bark  
scribing "S9 BT"  
10" Maple bears S.34°W., 13.6 ft. showing scribing  
"S8 BT" on open face.  
30" ± Cedar stump bears N.32°W., 24.8 ft., very  
rotten, shows axe marks.  
Set - 2½"x30" alum. pipe at position of found pipe with  
¾" alum. cap mkd: "US Forest Service T21S R10W  
S5 S4 S8 S9 RLS 1651 1983 UNLAWFUL TO DISTURB".  
13" Alder bears N.87°W., 21.1 ft., bark scribed  
"T21S R10W S5 BT"  
29" Alder bears N.34°E., 233.2 ft. bark scribed  
"T21S R10W S4 BT"