

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 3 Page(s) 1001)

Set a Fir post, for ¼ sec cor., from which
A Fir, 24" dia., bears S.25°E., 3 lks.
A Fir, 10" dia., bears N.42°W., 21 lks.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1128)

Intersect pint for old ¼ sec. cor., located by reference to the old BTs. At the exact cor. point set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ Sec. cor., with brass cap mkd:
$$\frac{1}{4} \frac{S \ 4}{S \ 9}$$

1919
from which
A Fir, 30" dia., bears S.25°E., 13 lks., mkd: ¼ S9 BT. OBT
A Fir, 18" dia., bears N.42°W., 21 lks., mkd: ¼ S4 BT. OBT

Douglas Co. Surveyors Office - Karen Reed, Deputy - John Powell - Aug. 18, 1982 - C.S. File 62/1-12

Found - 1919 GLO brass cap with properly marked brass cap rusted off. IP is firmly set with brass cap lying alongside. (notes call for date on cap to be 1919 but I find 1918)
Orig. 30" Fir now 42" with good scar bears S.20°E., 12.7 ft., (rec. S.25°E., 8.6 ft)
Orig. 18" Fir now 26" rotted snag 10 ft. tall. No scribing or face visible, bears N.48°W., 12.4 ft. (rec. N.42°W., 13.9 ft)
Set - At the location or the found IP I set a 1"x30" IP with brass cap attached cap mkd: "Douglas Co. Surveyor T21S ¼ S4 S9 R10W 1982". I place remains of old pipe along West side of new pipe & bury old brass cap along East side.
15" Fir scribed "¼ S9 CS BT" in double blaze bears S.3°W., 11.7 ft.
5" Hemlock scribed "¼ S4 CS BT" in double blaze bears N.30°W., 25.2 ft.