

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 352100

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 4 only, T22-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 3 Page(s) 1752)

Set a stone 24x24x8 ins., 18" in the ground for ¼ sec. cor. marked ¼ S. on N. face, from which
An Alder 4" dia., bears N.77°E., 22 lks. dist. mkd. ¼ S BT
An Alder 4" dia., bears S.53°E., 11 lks. dist. mkd. ¼ S BT

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1044)

Apportioned distance.
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ sec. cor. of sec. 4 only, with brass cap mkd: ¼ _____
S 4
1919
from which
A Wild Cherry 6" dia., bears S.54°E., 23 lks. dist. mkd. ¼ S4 BT.
A Wild Cherry 6" dia., bears S.62°W., 15 lks. dist. mkd. ¼ S4 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - June/July 1968 - C.S. 54/1-18

Found - Concrete filled I.Pipe with brass cap broken off, Deposit alongside.
No trace of Cherrywood around location of SW. orig. BT.
Call on spur ridge to West fits good.
Set Brass cap at cor. mkd: County Surveyors Office
T 21 S
T 22 S R10W ¼ _____
S 4
New BTs -15" D.Fir S.87°E., 18.5 ft. mkd. ¼ S4 CS BT.
32" D.Fir S.22°W., 16.5 ft. mkd. ¼ S4 CS BT.
This corner lies about 160 ft. E. of spur, ridge, sloping S.