

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1106-7)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 27, 28, 33 & 34, with brass cap mkd:

T21S R10W
S 28 | S 27
S 33 | S 34
1919

from which

- A Fir, 14" dia., bears N.66°E., 27 lks., mkd: T21S R10W S27 BT.
- A Fir, 12" dia., bears S.12°E., 7 lks., mkd: T21S R10W S34 BT.
- A Fir, 12" dia., bears S.32°W., 32 lks., mkd: T21S R10W S33 BT.
- A Fir, 8" dia., bears N.45°W., 3 lks., mkd: T21S R10W S28 BT.

Fd. Ok by Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - July 1968 C.S. File 54/1-15A and Feb. 1970 - C.S. File 54/1-21A