

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1106)

40.00 chs
Point for $\frac{1}{4}$ sec. cor. in wash, course SW; where it is impracticable to establish permanent corner.

41.00 chs
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for witness corner to the $\frac{1}{4}$ Sec. cor., with brass cap mkd:

W C
 $\frac{1}{4}$
S 28 | S 27
1919

from which
A Cedar, 30" dia., bears S.72°E., 26 lks., mkd: WC $\frac{1}{4}$ S27
BT.
An Alder, 10" dia., bears N.79°W., 51 lks., mkd: WC $\frac{1}{4}$ S28
BT.