

PRIMARY CORNER DESCRIPTION North Cor. Secs. 27 & 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1100)

Set a country rock, 16x14x8 ins., 11" in the ground for cor. of secs. 27 & 28, marked with 3 notches on E edge; from which
An Alder, 10" dia., bears S.35°E., 20 lks., mkd: T21S R10W S27 BT.
A Fir, 14" dia., bears S.64°W., 31 lks., mkd: T21S R10W S28 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - July 1968 - C.S. File 54/1-4

Found - Corner stone, broken in half with 3 chiseled notched on East edge, stone in place.
Orig. 14" now 28" Fir, alive, S.64°W., 20.5 ft., shows good scar. We do not open. Rescribe "T21S R10W S28 CS BT"
Orig. Alder to SE gone, hole where it stood fits bearing & dist.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T21S R10W
OFFICE 1968 S 28|S 27
Deposit cor. stones at base of brass cap.
14" D.Fir S.3°E., 16.2 ft., mkd: T21S R10W S27 CS BT
Note - This corner lies on very steep NW slope about 75' W. of 33-79 on USFS "L" line for road, not yet constructed.

William L. Shull, LS 909 - For: USFS - Oct. 24, 1986 - C.S. File 62/30-18

Found - A weathered sandstone, lying loose on the ground, no marks, its position too uncertain to be considered the corner. (1918 Mensch GLO survey)
33" D.Fir, S.64°W., 31 lks (20.5 ft.) bark scribed "T21S R10W .. S28 CS", probably about 1968. A lower blaze has been cut into, with axe marks visible on the old face, but date of marks uncertain. I believe this to be the GLO BT.
Possible Alder roots, rotten, S.35°E., 20 lks.
Set - From the standing BT, I set an alum. Forest Service monument, 2½" x 30" with ¾" alum. cap, set 25" deep, using the found stone & other sandstones as a small collar. **continued next page**

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION North Cor. Secs. 27 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 20" D.Fir, bears S.33°W., 28.1 ft., scribed "T21S R10W S28 BT" with brass washer (LS 909), Land Survey Monument sign, BT sign, and red paint.

Note - The corner is on a steep (45°) North Westerly facing slope in old growth timber & brush, about 75 ft., West of FS road #4100-147.