

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Thiel under contract 342 dated Oct. 6, 1879 - (DCSO records Vol. 3 Page(s) 1016)

Set ¼ sec. post, at the foot of a cliff, 6 ft. high and 10 ft. long, from which;

An Alder, 3" dia., bears N.49°W., 15 lks.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1067 & 1110)

Pg. 1067

South retracing the line bet. secs. 21 & 22; at 40.00 chs find no trace of the ¼ sec. cor., set temp. ¼ cor.

Pg. 1110

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ Sec. cor., with brass cap mkd:

¼
S 21|S 22
1919

from which

A Fir, 24" dia., bears N.14°E., 40 lks., mkd: ¼ S22 BT.

A Maple, 12" dia., bears N.45°W., 40 lks., mkd: ¼ S21 BT.

No trace of the old ¼ sec. corner could be found.

Herman A. Pieske, RLS #1651 - For: Siuslaw National Forest
USDA - Dec. 1983 - M 95-80 A & B

Found - 24" Big Leaf Maple bears N.45°W., 26.4 ft. healed face.

30" Fir, blown down, healed face. Root hole bears N.14°E., 26.4 ft.

Set - 2½"x30" alum. pipe, 24" in the ground, with 3¼" alum. cap mkd: "US Dep of Agri-Forest Service T21S R10W ¼ S21 S22 1983 RLS 1651 Unlawful to Disturb"

New BT - 14" Hemlock bears N.40°E., 47.6 ft., faced and scribed "¼ S22 BT"