

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 3 Page(s) 1001)

Set stone, 24x12x12 for corner to secs. 3, 4, 9 & 10.
A Hemlock, 8" dia., bears N.83°E., 34 lks.
Land very rough and broken.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1067 & 1114-5)

Pg. 1067
I reestablish the corner of secs. 3, 4, 9, & 10
Pg. 1114-5
The apportioned point for cor. of secs. 3, 4, 9, & 10 Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 3, 4, 9 & 10, with brass cap mkd:

T21S R10W
S 4 | S 3
S 9 | S 10
1919

from which
A Fir, 36" dia., bears N.10°E., 15 lks., mkd: T21S R10W S3 BT.
A Chittem, 8" dia., bears S.73°E., 21 lks., mkd: T21S R10W S10 BT.
A Hemlock, 7" dia., bears S.42°W., 69 lks., mkd: T21S R10W S9 BT.
A Fir, 60" dia., bears N.40°W., 46 lks., mkd: T21S R10W S4 BT.

Douglas Co. Surveyors Office - Karen Reed, Deputy - John Powell - Aug. 17, 1982 - C.S. File 62/1-9

Found - A 1" dia., concrete filled IP badly rusted protruding .9 ft. above ground. No evidence of 1919 brass cap.
A 36" dia., Fir now 60" bears N.10°E., 9.9 ft., with well healed single blaze. 1919 GLO
A 7" dia., Hemlock, now 26" bears S.45°W., 45.5 ft. (rec. S.42°W.) with a well healed single blaze. 1919 GLO
A 60" dia., Fir, now 62" bears N.40°W., 31.2 ft. dist. (rec. 30.4 ft.) with a well healed single blaze. 1919 GLO

continued next page

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set - I reference out IP and replace said pipe with a 1"x30" IP with brass cap mkd: "DOUGLAS CO. SURVEYORS OFFICE: T21S R10W S4 S3 S9 S10 1982" protruding 6" above ground in a 1.5 ft. dia., mound of stone. I lay rusted pipe along east side of brass cap.

New BT - A 17" Maple the center trunk of a triple trunk tree, scribed "T21S R10W S10 CS BT" in a double blaze bears S.27°E., 18.9 ft. dist. Bearing and dist. taken to center of root crown.

Note - Corner falls on a moderately steep west slope.