

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 4 only

Alias	Description

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1116-7)

Apportioned distance
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 Sec. cor. of sec. 4 only, with brass cap mkd:

1/4
S 4 |
1919

from which
An Alder, 12" dia., bears S.60°W., 42 lks., mkd: 1/4 S4 BT.
A Maple, 10" dia., bears N.73°W., 30 lks., mkd: 1/4 S4 BT.

Douglas Co. Surveyors Office - Karen Reed, Deputy - John Powell - Aug. 17, 1982 - C.S. File 62/1-10

Found - 1919 GLO brass cap properly marked, rusted off. IP is firmly set with brass cap lying alongside.
Possible orig. 12" Alder now 16" leaning to the SW with well healed scar bears S.59°W., 28.5 ft. (Rec. S.60°W., 27.7 ft.) I add bark scribing "CS BT" below scar.

Set - At the location of found 1" IP, I set a 1"x30" IP with brass cap attached mkd: "DOUGLAS CO SURVEYOR T21S 1/4 S4 R10" 1982" I place remains of old IP along West side of new pipe & I bury found brass cap along east side.

New BTs- 11" Alder bark scribed "1/4 S CS BT" bears S.17°E., 24.2 ft.
1/2" Iron rod protruding 3 ft. out of ground with an International Paper Co. property line sign, bears S.3°W., 3.0 ft.

Note - 1/4 Sec. 3 only, bears N.3°E., 69.7 ft.