

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4; 33 & 34, T20-10

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 12, 1867 (DCSO records Vol. 1 Page(s) 175)

Set post for cor. to secs. 3, 4, 33 and 34, from which
A Vine Maple 5" dia., bears S.74°W., 68 lks. dist.
A Vine Maple 3" dia., bears N.70°W., 44 lks. dist.
An Alder 18" dia., bears N.14°E., 50 lks. dist.
A Vine Maple 6" dia., bears S.44°E., 24 lks. dist.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (Group #36) (surveyed 1919) - (DCSO records Vol. 1 Page(s) 255) and (Dup. Pgs. 1059-60)

The sec. cor., the point for which is located by reference to the old NE. and NW. bearing trees, which are dead and badly decayed. At the exact cor. point, SET an iron post 3 ft. long, 2" dia., 24" in the ground for cor. of secs. 3, 4, 33 and 34, with brass cap mkd:

T20S R10W
S33 S34
S4 S3
T21S
1919

from which
A Chittem 12" dia., bears N.22°E., 82 lks. dist. mkd. T20S R10W S34 BT.
An Alder 24" dia., bears S.64°E., 17 lks. dist. mkd. T21S R10W S3 BT.
A Chittem 6" dia., bears S.39°W., 47 lks. dist. mkd. T21S R10W S4 BT.
A Vine Maple 6" dia., bears N.74°W., 39 lks. dist. mkd. T20S R10W S33 BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11671)

The Sec. cor., monumented with an iron post, 2" dia., 8" above ground, firmly set, with brass cap mkd. in 1918, from which the remaining 1918 bearing tree:

An Alder 24" dia., bears S.67½°E., 17 lks. dist. with the scribe marks R10W S3 BT visible on partly overgrown blaze. (Rec. brg. S.64°E.)

The iron post is rusted nearly through; in its place
(Cont. Next Page)

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4; 33 & 34, T20-10

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Set an iron post 3 ft. long, 2" dia., 28" in the ground with
brass cap mkd:

T 20 S R 10 W
S 33 S 34
S 4 S 3
T 21 S

1951

from which new bearing trees:

A Fir 14" dia., bears N.45°E., 132 lks. dist., mkd. T20S
R10W S34 BT.

A Fir 24" dia., bears S.58°45'W., 98 lks. dist. mkd. T21S
R10W S4 BT.

A Hemlock 20" dia., bears N.84¼°W., 98 lks. dist. mkd.
T20S R10W S33 BT.

Deposit the old iron post at the base of the new iron post.

Survey by Herman Pieske - For: Siuslaw National Forest - Nov.
1983 - M 95-59 A&B

Found - 2" Iron pipe loosely set 18" above ground with 1951
3" brass cap, properly mkd. Firmed up.

36" D.Fir bers N.67°E., (75° record) 148.49 ft.,
healed.

35" Hemlock bears N.84°W., 64.3 ft. scribed visible
"R10W S33 BT US."

36" D.Fir bears S.59°W., 62.7 ft., healed blaze.

New BT - 36" big leaf Maple, bears S.19°E., 27.8 ft. blazed
and scribed "T21S R10W S3 BT."

Fd. OK, Aug. 1992 by L. Roberts - M 115-64

Survey by Les Roberts - For: I.P. Timberlands Operating Co.
Ltd. - Jan. 1994 - M 118-47

Corner Report Only

Found - 1951 GLO brass cap.

30" Hemlock N.85°W., 64.3 ft., scribe visible.

33" Fir N.70°E., 148.5 ft., scar visible. 1951 rec.
87.1 ft.) 1951

38" Fir S.59°W., 64.5 ft., scar visible. 1951

36" Maple S.20°E., 26.5 ft., scribe visible. 1983