

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 434600

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec. 3 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1116)

-----  
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for  
¼ Sec. cor. of sec. 3 only, with brass cap mkd:

¼ S 3  
1919

from which

An Alder, 6" dia., bears N.67°E., 14 lks., mkd: ¼ S3 BT.  
A Hemlock, 6" dia., bears N.14°W., 15 lks., mkd: ¼ S3 BT.

Herman A. Pieske, RLS #1651 - For: USFS - Dec. 1983 - M 95-79  
A & B

-----  
Found - IP with 1919 GLO brass cap, pipe rusted & broken off  
& laying next to it.

12" stob, very decayed, bears N.14°W., 9.9 ft.

Set - 2" alum. pipe, 26" in the ground, over rusted iron  
pipe & brass cap mkd: "USDA FOREST SERVICE T21S  
R10W ¼ S3 RLS 1651 1983 UNLAWFUL TO DISTURB".  
Buried IP & brass cap along side alum. pipe.

New BTs- 15" Hemlock bears N.67°W., 27.9 ft. blazed & scribed  
"¼ S3 BT"

7" Cedar bears N.5°W., 35.4 ft. blazed & scribed "¼  
S3 BT"