

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Thiel under contract 342 dated Oct. 6, 1879 - (DCSO records Vol. 3 Page(s) 1018)

Set for 1/4 sec. post a rock, 18x12x8, from which
A double Alder, 5" dia., bears N.89 1/2°W., 22.73 lks.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1067 & 1099)

Pg. 1067
Retracing the line bet. secs. 22 & 27; at 40.00 chs. find no trace of the 1/4 sec. cor., set temp 1/4 corner.

Pg. 1099
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 Sec. cor., with brass cap mkd:

1/4 $\frac{S\ 22}{S\ 27}$
1919

from which
An Alder, 10" dia., bears S.73°W., 18 lks., mkd: 1/4 S27 BT.
A Fir, 10" dia., bears N.74°W., 27 lks., mkd: 1/4 S22 BT.
No trace of old 1/4 sec. cor. could be found.

Les Roberts - For: International Paper Co. - December 1991 - M 114-28 - C.S. File 63/138-1

Found - IP & brass cap, top broken off. 1918 GLO
25" Fir "shell" bears S.82°W., 17.5 ft., (scar visible) 1918 BT Rec. N.74°W., 17.8 ft.

No evidence of 10" Alder.
Set - 5/8"x36" alum. rod with alum. cap beside GLO iron pipe. Buried purple magnetic marker under 36" alum. rod.

10" Fir bears N.7°E., 77.4 ft., scribed/painted red.
16" Alder bears N.56°E., 23.4 ft., bark scribed, painted red.
18" Alder bears S.13°E., 16.3 ft., bark scribed, painted red.
42" Fir bears S.73°W., 31.7 ft. scribed/painted red.

Note - Corner lies on West slope about 150 ft. west of ridge. Ridge bears North South.