

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1115-6)

Apportioned distance
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 Sec. cor., of Sec. 10 only, with brass cap mkd:

1/4 S 10

1919

from which
An Alder, 10" dia., bears S.40°E., 3 lks., mkd: 1/4 S10 BT.
An Alder, 12" dia., bears S.15°W., 14 lks., mkd: 1/4 S10 BT.
This 1/4 sec. cor. stands on top of spur, slopes N; along N slope.

Ronald Stuntzner - For: IP - Jan. 12, 1977 - M 62-78

Found - BC & 12" Alder as set by US GLO in 1919
Scribed- Hemlock 10" N.36°E., 16.3 ft. & tagged.
Hemlock 12" S.83°E., 22.8 ft. & tagged.

Douglas Co. Surveyors Office - Karen Reed, Deputy - John Powell - Aug. 18, 1982 - C.S. File 62/1-13

Found - 1919 GLO brass cap properly marked on a 1" dia., concrete filled iron pipe. Top 1 foot of pipe broken off, remaining portion firmly set in ground. Condition of pipe is badly rusted.
An orig. 12" Alder, now 17" bears S.28°W., 9.2 ft. (rec. S.15°W.,) with well healed single blaze. This tree is leaning in a NW direction.
A 12" Hemlock 15" bears S.83°E., 22.8 ft. scribed "S10 1/4" in a single blaze. 1977
A 10" Hemlock 13" bears N.36°E., 16.3 ft. scribed "S10 1/4" in a single blaze. 1977
Set - Although the orig. BT was off bearing, the IP was firmly set & appeared undisturbed. Therefore I drive a 1 1/2"x30" IP w/brass cap stamped "DOUGLAS CO. SURVEYORS OFFICE T21S R10W 1/4 S10 1982" in the position of the pipe. I drive orig. pipe along west side of brass cap & bury the top 1 ft. of orig. pipe with cap along southerly side of new brass cap.
No new BTs. Corner falls on steep north slope. Land south of corner to be logged.