

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1084)

-----  
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 26, 27, 34, & 35, with brass cap mkd:

T21S R10W  
S 27|S 26  
S 34|S 35  
1919

from which

- A Fir, 6" dia., bears N.25°E., 10 lks., mkd: T21S R10W S26 BT.
- A Fir, 12" dia., bears S.59°E., 19 lks., mkd: T21S R10W S35 BT.
- A Fir, 8" dia., bears S.12°W., 15 lks., mkd: T21S R10W S34 BT.
- A Fir, 14" dia., bears N.36°W., 21 lks., mkd: T21S R10W S27 BT.