

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Thiel under contract 342 dated Oct. 6, 1879 - (DCSO records Vol. 3 Page(s) 1018)

Mark an Alder 4" in dia., standing on top of a narrow burnt spur, course E & W, for corner to secs. 22, 23, 26 & 27, from which:

- A Fir, 24" dia., bears N.1°E., 20 lks.
- A Fir, 16" dia., bears S.26°W., 77 lks.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1068)

At the point for SE cor. of Sec. 22, located by reference to the old BTs, which are as described by the Surveyor General, but in bad sate of preservation, set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 22, 23, 26, & 27, with brass cap mkd:

T21S R10W
S 22|S 23
S 27|S 26
1919

from which

- A Fir, 12" dia., bears N.65°E., 25 lks., mkd: T21S R10W S23 BT. (New BT)
- A Fir, 10" dia., bears S.10°E., 5 lks., mkd: T21S R10W S26 BT. (New BT)
- A Fir, 14" dia., bears S.34°W., 28 lks., mkd: T21S R10W S27 BT. (New BT)
- A Fir, 12" dia., bears N.45°W., 32 lks., mkd: T21S R10W S22 BT. (New BT)