

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 23 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1088)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for
¼ Sec. cor. sec. 23 only, with brass cap mkd:

¼
|S 23
1919

from which

- A Hemlock, 5" dia., bears N.54°E., 29 lks., mkd: ¼ S23 BT.
- A Hemlock, 14" dia., bears S.6°E., 33 lks., mkd: ¼ S23 BT.

Herman A. Pieske, RLS #1651 - For: Siuslaw National Forest
USDA - Dec. 1983 - M 95-80 A & B

Set - 2½"x30" alum. pipe, 27" in the ground, with 3" alum.
cap mkd: US Dep of Agri-Forest Service T21S R10W ¼
S23 RLS 1651 1983 Unlawful to Disturb.

24" Hemlock bears S.52°E., 6.1 ft. faced & scribed: ¼
S23 BT.

42" Hemlock bears N.14°E., 20.5 ft., faced & scribed:
¼ S23 BT.