

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11 & 14 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1092-3)

(A point 80.00 chs. northing from the corner of secs 14 & 23)
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 11 & 14, with brass cap mkd:

T21S
|S 11
|S 14
|R10W
1919

from which

A Chittem, 10" dia., bears N.39°E., 31 lks., mkd: T21S R10W S11 BT.

A Chittem, 6" dia., bears S.24°E., 31 lks., mkd: T21S R10W S14 BT.

Herman A. Pieske, RLS #1651 - For: Siuslaw National Forest
USDA - Dec. 1983 - M 95-80 A & B

Set - 2½" x 30" alum. pipe, 20" in the ground with sand stone mound, with alum. cap mkd: "US Dep. of Agri. Forest Service S11 S14 RLS 1651 1983 Unlawful to Disturb."
16" Cedar bears S.22°E., 16.3 ft., faced & scribed "T21S R10W S14 BT."
30" Hemlock bears N.12°40'E., 179.0 ft., faced & scribed "T21S R10W S11 BT."