

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 500572

PRIMARY CORNER DESCRIPTION Cor. Secs. 3 & 10 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1095-6)

(A point 73.89 chs. east of the cor. of secs. 3, 4, 9, & 10)
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 3 & 10, with brass cap mkd:

T21S
S 3 |
S 10 |
R10W |
1919

from which

An Alder, 10" dia., bears S.7°W., 24 lks., mkd: T21S R10W S10 BT.

An Alder, 10" dia., bears N.66°W., 41 lks., mkd: T21S R10W S3 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones - W. Penley - 10/2/1969 - C.S. File 54/1-40

Found - GLO brass cap set in 1919, cap rusted away.
10" now 28" Alder, N.66°W., 27.1 ft. shows old face.
No trace of SW BT.

Set - Brass cap at cor. mkd: COUNTY SURVEYOR'S T21S R10W OFFICE, 1969 S 3 | S11 S 10 |

48" Cedar S.73°W., 27.7 ft. mkd: T21S R10W S10 CS BT

58" Cedar East 8.5 ft., mkd: T21S R10W S11 CS BT.

No trace available in NW quadrant.