

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, T20-10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 12, 1867 (DCSO records Vol. 1 Page(s) 175)

-
- Set post for cor to secs. 2, 3, 34 and 35; from which
- A Hemlock 30" dia., bears N.25°W., 81 lks. dist.
 - A Hemlock 8" dia., bears N.73°E., 8 lks. dist.
 - A Hemlock 30" dia., bears S.72°E., 52 lks. dist.
 - A Hemlock 24" dia., bears S.24°W., 45 lks. dist.

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 208)

-
- I set post 4 ft. long, 4" sq., 24" in the ground for cor. of secs. 34, 35, 2 and 3, and marked T20S S35 on NE.; R10W S2 on SE.; T21S S3 on SW.; S34 on NW. faces, with 4 notches on W. and 2 on E. edges; from which
- A Fir 60" dia., bears S.37½°E., 381 lks. dist. mkd. T21S R10W S2 BT.
 - Cedar, dead, 36" dia., bears N.36°E., 175 lks. dist. mkd. T20S R10W S 3 BT.
- No other trees in limits and no stone near to be found.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (Group #36) (surveyed 1919) - (DCSO records Vol. 1 Page(s) 257) and (Dup. Pg. 1062)

-
- Intersect the point for old cor. of secs. 2, 3, 34 and 35, located by reference to the SE. and NE. bearing trees, the NE. tree having fallen. I change this cor. to refer to secs. 34 & 35 only and at the exact cor. point, Set an iron post 3 ft. long, 2" dia., 24" in the ground with brass cap marked:
- T20S R10W
S34 S35
1919

- from which
- A Fir 6" dia., bears N.25°E., 117 lks. dist. mkd. T20S R10W S35 BT.
 - A Fir 8" dia., bears N.8°W., 184 lks. dist. mkd. T20S R10W S34 BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11668)

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 506700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only, T20-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The cor. of secs. 34 & 35, monumented with an iron post, 2" dia., 10" above ground, firmly set, with brass cap mkd. in 1918, from which 1918 bearing trees:

A Fir 30" dia., bears N.26°E., 117 lks. dist. plainly blazed and healed. (Rec. brg. N.25°E.)

A Fir 30" dia., bears N.8°W., 184 lks. dist., plainly blazed and healed.

and 1892 bearing tree

A Fir 60" dia., bears S.36½°E., 381 lks. dist., bearing a plain old blaze, but no scribe marks visible and these may have been cut out when cor. was changed to refer only to secs. in T20S R10W.

The old iron post is rusted nearly through; in its place, Set an iron post 3 ft. long, 2' dia., 28" in the ground with brass cap mkd. T 20 S R 10 W

S 34 S 35
T 21 S R 10 W
S 2
1951

Deposit old iron post at base of new iron post.