

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1097)

-----  
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 Sec. cor., with brass cap mkd:

1/4  $\frac{S \ 2}{S \ 11}$   
1919

from which

A Hemlock, 14" dia., bears S.17°E., 50 lks., mkd: 1/4 S11 BT  
A Hemlock, 40" dia., bears N.70°W., 19 lks., mkd: 1/4 S2 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - March 1968 - C.S. File 54/1-12

-----  
Found - 1" iron pipe, filled with concrete with brass cap broken off & remains of orig. BTs.  
Orig. 14" Hemlock, now only decayed remains of stump with part of old axe blaze, S.17°E., 33.0 ft., no scribe.  
Orig. 40" Hemlock N.70°W., 12.5 ft., now only partial decayed shell of stump, no scribe found.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T21S R10W  
OFFICE 1968 1/4  $\frac{S \ 2}{S \ 11}$

5" Hemlock N.69°E., 20.1 ft., mkd: 1/4 S2 CS BT.  
14" Hemlock S.52°E., 45.3 ft., mkd: 1/4 S11 CS BT.

Note - Deposit old pipe & cap alongside new monument.  
This corner lies on E. side of creek 2 ft. wide, course NW.