

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 547100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 2 only, T22-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1750)

A Fir 20" dia., on line which I marked $\frac{1}{4}$ S. on N. face for $\frac{1}{4}$ sec. cor. from which,

A Fir 30" dia., bears N.75°E., 23 lks. dist., mkd. $\frac{1}{4}$ S BT.

A Fir 3" dia., bears S.75°W., 15 lks. dist., mkd. $\frac{1}{4}$ S BT.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1040)

Intersect the old $\frac{1}{4}$ sec. cor. which is a Fir snag, mkd. and witnessed as described by the Surveyor General. I change this corner to refer to Sec. 2 only and alongside the old cor. Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for $\frac{1}{4}$ cor. of Sec. 2 only, with brass cap marked:

$\frac{1}{4}$ _____
S 2
1919

from which

A Fir 8" dia., bears S.5°W., 15 lks. dist. mkd. $\frac{1}{4}$ S2 BT.
(New BT)

A Fir 16" dia., bears S.73°W., 12 lks. dist. mkd. $\frac{1}{4}$ S2 BT.
(Old BT)

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - May 1968 - C.S. File 54/1-28

Found - 1919 GLO brass cap, broken off, concrete-filled pipe in place, alongside corner tree, a badly decayed stump.

Orig. (1894) 40" Fir, now badly decayed snag, N.75°E., 15.2 ft., we open and find " $\frac{1}{4}$ S7" scribe.

1919 BT, 8" now 9" Fir S.5°E., 9.9 ft. (Rec. S.5°W.) now snag, we open and find " $\frac{1}{4}$ S7" scribe.

1919 BT, 16" now 22" Fir, alive, S.73°W., 7.9 ft., shows scar. We rescribe " $\frac{1}{4}$ S2 CS BT"

Set Brass cap at cor. mkd: County Surveyors Office

T21S
T22S R10W $\frac{1}{4}$ _____
S 2

1968

(Cont. Next Page)

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 547100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 2 only, T22-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set B.C. on North side of corner stump at place where bearings and distances meet. Deposit corner materials alongside brass cap.
New BT - 16" D.Fir S.22°E., 26.2 ft. mkd. ¼ S2 CS BT.
This cor. lies on very steep SE. slope approx. 75.0 ft. West of ravine, course North.