

TOWNSHIP 21 RANGE 10 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1072)

-----  
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 25, 26, 25, & 36, with brass cap mkd:

T21S R10W  
S 26|S 25  
S 35|S 36  
1919

from which

- A Fir, 14" dia., bears N.15°E., 22 lks., mkd: T21S R10W S25 BT.
- A Fir, 10" dia., bears S.22°E., 12 lks., mkd: T21S R10W S36 BT.
- A Fir, 14" dia., bears S.2°W., 28 lks., mkd: T21S R10W S35 BT.
- A Fir, 12" dia., bears N.78°W., 14 lks., mkd: T21S R10W S26 BT.